

Seria DFG-R

Heating mats for mirrors



■ Application:

- It prevents fogging the mirror



IP54

ELECTRICAL SPECIFICATION

MODEL	R30	R40	R50
Size	30 cm	40 cm	50 cm
Input Voltage	230V / 50Hz		
Input Power	1.5 ÷ 2.5W/dm ²		
Power	10 ÷ 17W	18 ÷ 31W	29 ÷ 49W
Averaged power consumption	10.79W	33.5W	41W
Average value of temperatura rising	10°C ÷ 20°C		
Wire	OMYp 2x0.5mm ² (2x20AWG)		
Wire lenght	800 mm		
Material	PET (Dupont)		
Mat thickness / total thickness	0.07 m ²	0.125 m ²	0.196 m ²
Thickness	0.4mm / 6.1mm		
Evaporation time	Od 1 do 10 min		
Sticking strength	0.5kg/cm ²		
Softening	180°C		
Hot melting temperature is over	260°C		
Warranty	2 years		

WORKING ENVIRONMENT

Working Temperature	-25°C ÷ 60°C
Working Humidity	10 ÷ 90% RH non-condensing
Storage Temperature and Humidity	-20°C ÷ 85°C, 5 ÷ 90% RH non-condensing
Degree of IP protection	IP54

OTHER

EAN

